

MUTOH Product Bulletin

14oz Mutoh Smooth DS Banner

14oz Mutoh Smooth DS Banner is a 16-mil 2-sided Vinyl Banner Media. This opaque media has a high tenacity polyester core sandwiched with White Vinyl on both sides. This Banner Media is designed to accept most solvent-based inkjet and UV curable inks used in wide format digital printing systems.

Product Codes	M14SDSB38 (38" X 150' roll) M14SDSB54 (54" X 150' roll) M14SDSB64 (64" X 150' roll)
Weight	14oz / square yard [FS-191-5041]
Base Fabric	100% Polyester - Knit [DIN EN ISO 1049-2 / 2060] [24x30 / 250Dx250D]
Tensile Strength	85 lbs x 80 lbs [FS-191-5102 -grab]
Tear Resistance	7 lbs x 7 lbs [FS-191-5134 -tongue]
Adhesion	at least 6 lbs / inch [FS-191-5970]
Temperature Resistance	-22° F ~ 158° F [FS-191-5874]
U.V. Resistance	Not excessive fading after 1,000 HRS [Weather-O-Meter]
Flame Resistance	Pass
Finish	Matte Finish

Recommendations

This media is designed for interior and smaller short-term exterior sign and banner applications. In any exterior application, care should be taken to reinforce hems with webbing and "D" rings attached to the webbing. Grommets should be through the webbing reinforced hems. Fasten securely at all four corners and at grommet points to prevent wind flapping. Wind-whip can cause a banner to self-destruct.

Store in a cool dry area. Prolonged exposure to heat will shorten the shelf life and printability of this media. Standard shelf life is 1 year.

When printing two-sided, allow the first printed side to cure completely before printing the second side. Printing the second side before the first is completely cured may allow the inks to re-wet and block.

MUTOH

2602 South 47th Street • Phoenix, AZ 85034 • (480) 968.7772 • (800)99.MUTOH • FAX (480)968.7990
Web Site: www.mutoh.com • e-mail: sales@mutoh.com

This information is offered for your general guidance only. It is accurate to the best of our knowledge at the time of printing but is not intended to relieve the user from its' responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to safe handling of this material. Since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied.