

MUTOH Product Bulletin

MUTOH 3.4 Mil Matte Vinyl Permanent PERMANENT ADHESIVE

MUTOH 3.4 Mil Matte Vinyl Permanent is a 3.4-mil premium white matte flexible calendared PVC film coated with permanent acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems. The adhesive produces permanent bond to a variety of common substrates used in the graphics applications. The 90# liner offers excellent product layflat in a variety of ambient conditions.

Product Codes

MMCV30-PA	(30" X 150' roll)
MMCV54-PA	(54" X 150' roll)
MMCV60-PA	(60" X 150' roll)

Applications MUTOH 3.4 Mil Matte Vinyl Permanent is designed for interior or exterior signage, decals, nameplates, die-cut letters and point-of-purchase displays.

Thickness

Film	3.4 mils.
Adhesive	9 to 1.1 mils.
Liner	6.7 mils.

(Thickness variance +/- 10%)

Dimensional Stability Good.

Temperature Ranges Minimum application temperature is +40°F.
Service temperature is -40°F to +180°F.

Expected Exterior Exposure Up to 5 years.

Adhesion To stainless steel - 40 oz/in.
PSTC-101 Method A with 24 hr. dwell at 70°F and 50% relative humidity.
Typical values. Individual values may vary.
Test thoroughly for your specific use.

Water Resistance Good. Test if immersed.

Humidity Resistance Good.

Solvent Resistance Good

Storage Stability 6-month shelf life when stored at 70°F and 50% relative humidity.

Recommendations

Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation.

MUTOH

2602 South 47th Street • Phoenix, AZ 85034 • (480) 968.7772 • (800)99.MUTOH • FAX (480)968.7990
Web Site: www.mutoh.com • e-mail: sales@mutoh.com

This information is offered for your general guidance only. It is accurate to the best of our knowledge at the time of printing but is not intended to relieve the user from its' responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to safe handling of this material. Since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied.